PECT

Polyco Polyflex Eco Cut Foamed Nitrile Palm Coated Cut Resistant Glove



PRODUCT INFORMATION

Item Number	**PECT**
Product Colour	**Green/Black**
Size Range	**6-12**
Primary Coating Polymer	**Nitrile**
Grip	**Foamed nitrile**
Cut Score	**F**
Heat Resistance	**Contact Heat Level 1**

FEATURES

Cut Resistant: Ultra-lightweight 18-gauge liner achieves the maximum levels of cut resistance according to EN388:2016, and excellent abrasion and tear resistance.

Environmental: Each glove contains a minimum of 13% recycled material (rPET)

Unique Feature: Flat nitrile reinforcement between the thumb and forefinger offers additional protection in an area that is highly susceptible to wear and tear

Lining: 18 gauge seamless knitted liner is ultra-lightweight, breathable and highly flexible, ensuring ultimate comfort at all times

Heat Resistant: Achieves Level 1 for Contact Heat according to EN407. Can withstand temperatures of 100ºC

Cut Resistant: Achieves cut level F according to EN388, for protection in the highest risk cut hazard applications

Environmental: Gloves supplied in paper bands
Recycled PET Liner

Abrasion Resistant: Achieves a maximum score of Level 4 for abrasion resistance as defined by European Standard EN388

Primary Coating Polymer: Primary Coating Polymer - Nitrile

FEATURES

Unique Feature: Tactile touchscreen compatible fingertips enable the wearer to use touch screen machinery or touch screen devices with precision and without the need to remove the glove
The Hydrophobic solution, which is applied through an intensive washing process, allows for a comprehensive and robust 3-Dimensional water resistant performance in wet and challenging conditions while maintaining maximum breathability

SECTORS

Automotive • Construction and Utility • Engineering and Manufacturing • Oil, Gas, and Renewables • Waste Management and Local Authority

STANDARDS

EN 388 Protective gloves against Mechanical Risks: 4X44F
EN 407 Protective gloves against Thermal Risks (heat and/or fire): X1XXXX
EN ISO 21420:2020: Protective gloves: General Requirements

CE PPE CAT II

EN 388:2016 + A1:2018 — 4X44F

EN 407:2020 — X1XXXX

UKCA

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

Polyco Healthline, South Fen Business Park, South Fen Road, Bourne, Lincolnshire, PE10 0DN
Tel: 0333 320 8550 • E: sales@polycohealthline.com • www.polycohealthline.com

POLYCO HEALTHLINE

PECT

Polyco Polyflex Eco Cut Foamed Nitrile Palm Coated Cut Resistant Glove

Polyco

CAUTION

May contain latex in elasticated cuff which can cause allergic reactions, including anaphylactic response.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

PACKING

1 pair per paper band
10 pairs per paper UIS band bundle
60 pairs per case
60 cases per pallet

Size	Outer Packaging Barcode
6	05010699859648
7	05010699859655
8	05010699859662
9	05010699859679
10	05010699859686
11	05010699859693
12	05010699999290

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

Polyco Healthline, South Fen Business Park, South Fen Road, Bourne, Lincolnshire, PE10 0DN
Tel: 0333 320 8550 • E: sales@polycohealthline.com • www.polycohealthline.com